



## Technical Specifications

**Package Includes:**..... Motor, Pump Tube, Hose, Storage Bracket, Barrel Adapter & Hand Nozzle

**Motor Type:**..... 220V, IP44 (825 W) or IP54 (450W)

**Pump Tube Material:**..... Aluminum, SS316, PTFE, Carbon Graphite

**Immersion Length:**..... 39" (1000 mm) or 47" (1200 mm)

**Discharge Hose:** .....PVC, 6 ft (1,8 m), 1" (25 mm) I.D.


**Hand Nozzle Material:** ..... Aluminum, Buna

**Maximum Flow Rate:**..... 22 GPM (83 LPM) *based on water*

**Maximum Viscosity:** ..... 1500 cps (mPas)

**Maximum Temperature:** ..... 175° F (80° C)

**Shipping Weight:**..... 23 lbs. (10,43 kg)



## DRUMS

Package P/N	Motor	Power	Pump Tube
9761	SP-280P-2-V	825 W	SP-6600-39
9761-B	SPE-450V	450 W	SP-6600-39

## IBC TANKS

Package P/N	Motor	Power	Pump Tube
9763	SP-280P-2-V	825 W	SP-6600-47
9763-B	SPE-450V	450 W	SP-6600-47



**Warning:** This pump is not suitable for use with Flammable/Combustible liquids.

\*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.