



Engineered for transferring mineral acids, light oils and suitable chemicals. Robust Stainless Steel (AISI 316) ensures excellent strength, durability and chemical resistance.
Pump tube conforms to ATEX directive 2014/34/EU.

Technical Specifications

Package Includes:..... Motor, Pump Tube, Hose, Hand Nozzle
..... Wall Bracket, Barrel Adaptor
Motor Type:..... 230V, 950 W, IP54, Variable Speed Drive
Pump Tube Material:.....SS316L, PTFE, Carbon Graphite
Immersion Length:..... 39" (1000 mm) or 47" (1200 mm)
Discharge Hose:PVC, 1,8 m, 1" (25 mm) I.D.
Hand Nozzle Material: SS316, PTFE
Maximum Flow Rate:..... 89 L/min *based on water*
Maximum Viscosity: 1500 cps (mPas)
Maximum Temperature: 80° C
Shipping Weight:..... 32 lbs. (14,51 kg)



EX II 2G EX h IIB T4 Gb

ATEX cert. applicable only for Pump tube (SP-7600-XX)

DRUM & IBC with AISI 316 Hand Nozzle

Package P/N	Motor	Power	Pump Tube
9570	SPE-950V	950 W	SP-7600-39
9571	SPE-950V	950 W	SP-7600-47

Drum & IBC with Aluminium Hand Nozzle

Package P/N	Motor	Power	Pump Tube
9572	SPE-950V	950 W	SP-7600-39
9573	SPE-950V	950 W	SP-7600-47



Warning: This pump is not suitable for use with Flammable/Combustible liquids.

*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.