



Engineered to transfer non-corrosive liquids such as machining lubricants, hydraulic fluid, motor oil, anti-freeze and light oils from barrels and IBC tote tanks. This package is specially designed to be light weight and portable, while still maintaining a robust quality and high rate of flow.

Pump tube conforms to ATEX directive 2014/34/EU.

Technical Specifications

Package Includes:..... Motor, Pump Tube, Hose, Hand Nozzle
..... Wall Bracket, Barrel Adaptor

Motor Type:..... 230V, 950 W, IP54, Variable Speed Drive

Pump Tube Material:..... Aluminum, SS316, PTFE, Carbon Graphite

Immersion Length:..... 39" (1000 mm) or 47" (1200 mm)

Discharge Hose:PVC, 1,8 m, 1" (25 mm) I.D.

Hand Nozzle Material: Aluminum, Buna

Maximum Flow Rate:..... 89 L/min based on water

Maximum Viscosity: 1500 cps (mPas)

Maximum Temperature: 80° C

Shipping Weight:.....10,43 kg



EX II 2G EX h IIB T4 Gb

ATEX cert. applicable only for Pump tube (SP-6600-XX)

DRUM & IBC tanks

Package P/N	Motor	Power	Pump Tube
9560	SPE-950V	950 W	SP-6600-39
9561	SPE-950V	950 W	SP-6600-47



Warning: This pump is not suitable for use with Flammable/Combustible liquids.

*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.