



## Common Applications

- To Be Used With Pumps
- Gravity Feed Applications
- Light Oils
- Hydraulic Fluids
- Non-Corrosive Liquids
- Diesel Oil, GTL, HVO & R33
- Heating Oil (EL/L)
- Engine Oil
- Gear Oil
- Antifreeze

## Features

- Safe filling and decanting
- Lightweight
- Available with 3/4" (19 mm) or 1" (25 mm) Hose Barb Intake
- swivel coupling for high pressure tightness
- Mounting Hook
- Low Pressure Loss

## Technical Specifications

<b>Wetted Material:</b> .....	Aluminum
<b>Seal Material:</b> .....	Buna-N
<b>Flow Rate:</b> .....	120 L/min
<b>Spout:</b> .....	25 mm
<b>Maximum Inlet Pressure:</b> .....	50 psi (3,4 bar)*
<b>Maximum Temperature:</b> .....	(52° C)
<b>Maximum Viscosity:</b> .....	.800 cps (mPas)

*\*NOTE: Consult factory regarding applications that require a higher inlet pressure.*

Model	Seals	Intake
SPE-9030A	Buna-N	1" (25 mm) Hose Barb
SPE-9030B	Buna-N	3/4" (19 mm) Hose Barb

**⚠ WARNING:** Prior to use, confirm chemical compatibility with the hand nozzles wetted material and seal material.